
TFA, GERMANY - KLIMALOGG PRO THERMO-HYGROMETER **Model: 30.3039.IT**



The NEW KLIMALOGG Pro temperature and humidity station can record up to 50,000 sets of data and transmit them via the wireless USB receiver (included) to your PC.

Recording intervals can be set at 1, 5, 10, 15, 30 minutes or 1, 2, 3, 6 hours. So recording every 1 minute would give you 34 days worth of data before a download was required. Or once every hour would give you well over 5 years of data before the data would need downloading. Free weather software is included allowing you to view the information in various formats on your pc as well as the ability to export it as a CSV file for use within EXCEL.

The KLIMALOGG can receive up to 8 wireless sensors; each transmitter can be labelled with it's own unique name in the software making it easy to identify and compare records. Sensors are weather proof so they can be mounted In or Outside and transmit up to 100 meters.

- > Measurement Units: °C and °F
- > Minimum/Maximum Manual Reset
- > Dew Point
- > Temperature & Humidity High / Low Alarm
- > Data Storage 50,000 measurements
- > Recording Interval: 1, 5, 10, 15, 30 minutes or 1, 2, 3, 6 hours
- > PC Software & USB receiver included
- > Can receive up to 8 outdoor sensors (all sensors sold separately none included with base station)
- > Transmission Range: up to 100m open field
- > Radio controlled 12 or 24 hour clock
- > Table standing or wall hanging

Specification:

- > Temperature Range: 0°C to 50°C
- > Temperature Accuracy: +/- 1°C
- > Humidity Range: 1 99%RH
- > Humidity Accuracy: +/- 3%RH(35 to 75%RH), otherwise, +/-5%RH
- > Transmission Frequency: 868MHz
- > Dimensions: H 137mm x W 98mm x 26mm
- > Weight 430g
- > Requires 3 x AA batteries (included)

Optional Transmitters





TFA, GERMANY - TEMPERATURE / HUMIDITY TRANSMITTER MODEL: 31.3180.IT



If you wish to measure the temperature in more than one place and read data via your KLIMALOGG PRO simply buy a temperature transmitter to add on to your existing weather station. You can position the sensors within 100 metres of the base station, so now you can monitor conditions in the garage, greenhouse, conservatory, wine cellar, wherever!

> Recording intervals can be set at 1, 5, 10, 15, 30 minutes or 1, 2, 3, 6 hours via the KLIMALOGG PRO console.

> Recording every 1 minute would give you 34 days worth of data before a download was required.

> Position sensors within 100 metres of the base station

Specifications:

- > Temperature Range: -39.6°C to 59.9°C
- > Humidity Range: 1 99%RH
- > Transmission Frequency: 868MHz
- > Transmission Interval: Every 10 seconds
- > Transmission Range: 100m
- > Requires: 2 x AA
- > Dimensions: L 43mm x W 23mm x H 160mm

TFA, GERMANY - TEMPERATURE TRANSMITTER WITH PROBE MODEL: 31.3181.IT

If you wish to measure the temperature in more than one place and read data via your KLIMALOGG PRO simply buy a temperature transmitter to add on to your existing weather station. This sensor comes with a probe so you can measure air, soil or water temperature.



Position the KlimaLOGG sensors within 100 metres of the base station, so now you can monitor conditions in the garage, greenhouse, conservatory, wine cellar, wherever!

> Recording intervals can be set at 1, 5, 10, 15, 30 minutes or 1, 2, 3, 6 hours via the KLIMALOGG PRO console.

> Recording every 1 minute would give you 34 days worth of data before a download was required.

> Position sensors within 100 metres of the base station

Specifications:

- > Temperature Range: -39.9°C to 59.9°C
- > Temperature Resolution: 0.1°C
- > Transmission Frequency: 868MHz
- > Transmission Interval: Every 10 seconds
- > Transmission Range: 100m
- > Requires: 2 x AAA
- > Dimensions: L 41mm x W 19mm x H 128mm